



Revision Number: 007.0

Issue date: 06/23/2021

## 1. PRODUCT AND COMPANY IDENTIFICATION

|                               |                                                                       |                     |               |
|-------------------------------|-----------------------------------------------------------------------|---------------------|---------------|
| <b>Product name:</b>          | <b>LOCTITE LB 8150 SV A/S known as Silver Grade Anti-Seize Lubric</b> | <b>IDH number:</b>  | 235005        |
| <b>Product type/use:</b>      | Lubricant                                                             | <b>Item number:</b> | 76764         |
| <b>Restriction of Use:</b>    | None identified                                                       | <b>Region:</b>      | United States |
| <b>Company address:</b>       | <b>Contact information:</b>                                           |                     |               |
| Henkel Corporation            | Telephone: +1 (860) 571-5100                                          |                     |               |
| One Henkel Way                | MEDICAL EMERGENCY Phone: Poison Control Center                        |                     |               |
| Rocky Hill, Connecticut 06067 | 1-877-671-4608 (toll free) or 1-303-592-1711                          |                     |               |
|                               | TRANSPORT EMERGENCY Phone: CHEMTREC                                   |                     |               |
|                               | 1-800-424-9300 (toll free) or 1-703-527-3887                          |                     |               |
|                               | Internet: www.henkelna.com                                            |                     |               |

## 2. HAZARDS IDENTIFICATION

### EMERGENCY OVERVIEW

**DANGER:** CAUSES SKIN IRRITATION.  
CAUSES SERIOUS EYE DAMAGE.

| HAZARD CLASS       | HAZARD CATEGORY |
|--------------------|-----------------|
| SKIN IRRITATION    | 2               |
| SERIOUS EYE DAMAGE | 1               |

### PICTOGRAM(S)



### Precautionary Statements

|                    |                                                                                                                                                                                                                                                           |
|--------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Prevention:</b> | Wash affected area thoroughly after handling. Wear protective gloves, eye protection, and face protection.                                                                                                                                                |
| <b>Response:</b>   | IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs: Get medical attention. Take off contaminated clothing. |
| <b>Storage:</b>    | Not prescribed                                                                                                                                                                                                                                            |
| <b>Disposal:</b>   | Not prescribed                                                                                                                                                                                                                                            |

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

| Hazardous Component(s)                                         | CAS Number | Percentage* |
|----------------------------------------------------------------|------------|-------------|
| Distillates (petroleum), hydrotreated heavy naphthenic         | 64742-52-5 | 30 - 60     |
| Graphite                                                       | 7782-42-5  | 10 - 30     |
| Calcium oxide                                                  | 1305-78-8  | 10 - 30     |
| Petroleum distillates, hydrotreated, light naphthenic          | 64742-53-6 | 10 - 30     |
| Aluminum not powder, dust or fume                              | 7429-90-5  | 5 - 10      |
| White mineral oil (petroleum) (not cmr)                        | 8042-47-5  | 1 - 5       |
| Quartz (SiO <sub>2</sub> ) respirable particulates (RCS) >=10% | 14808-60-7 | 0.1 - 1     |

IDH number: 235005

Product name: LOCTITE LB 8150 SV A/S known as Silver Grade Anti-Seize Lubric  
Page 1 of 6

\* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

#### 4. FIRST AID MEASURES

|                      |                                                                                                                                                                       |
|----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Inhalation:</b>   | Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.                                      |
| <b>Skin contact:</b> | Remove contaminated clothing and footwear. Immediately flush skin with plenty of water (using soap, if available). Get medical attention. Wash clothing before reuse. |
| <b>Eye contact:</b>  | Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.                                                                           |
| <b>Ingestion:</b>    | Do not induce vomiting. Never give anything by mouth to an unconscious person. Get immediate medical attention.                                                       |
| <b>Symptoms:</b>     | See Section 11.                                                                                                                                                       |

#### 5. FIRE FIGHTING MEASURES

|                                           |                                                                                                                                                      |
|-------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Extinguishing media:</b>               | Foam, dry chemical or carbon dioxide.                                                                                                                |
| <b>Special fire fighting procedures:</b>  | Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. In case of fire, keep containers cool with water spray. |
| <b>Unusual fire or explosion hazards:</b> | None                                                                                                                                                 |
| <b>Hazardous combustion products:</b>     | Oxides of carbon. Toxic and irritating vapors.                                                                                                       |

#### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

|                                   |                                                                                                                                                                                                                                                                        |
|-----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Environmental precautions:</b> | Do not allow product to enter sewer or waterways.                                                                                                                                                                                                                      |
| <b>Clean-up methods:</b>          | Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.<br>For small spills wipe up with paper towel and place in container for disposal.<br>For large spills absorb onto inert absorbent material and place in sealed container for disposal. |

#### 7. HANDLING AND STORAGE

|                  |                                                                                                                                                                         |
|------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Handling:</b> | Use only with adequate ventilation. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Keep container closed. |
| <b>Storage:</b>  | Keep in a cool, well ventilated area.                                                                                                                                   |

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

| Hazardous Component(s)                                         | ACGIH TLV                                                                                                                                                                                                                    | OSHA PEL                                                                                                                                                                                                                                           | AIHA WEEL | OTHER |
|----------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|-------|
| Distillates (petroleum), hydrotreated heavy naphthenic         | 5 mg/m <sup>3</sup> TWA Inhalable fraction.                                                                                                                                                                                  | 5 mg/m <sup>3</sup> PEL Mist.<br>500 ppm (2,000 mg/m <sup>3</sup> ) PEL                                                                                                                                                                            | None      | None  |
| Graphite                                                       | 2 mg/m <sup>3</sup> TWA Respirable fraction.                                                                                                                                                                                 | 5 mg/m <sup>3</sup> PEL<br>Respirable fraction.<br>15 mg/m <sup>3</sup> PEL Total dust.<br>5 mg/m <sup>3</sup> PEL Respirable fraction.<br>15 mg/m <sup>3</sup> PEL Total dust.                                                                    | None      | None  |
| Calcium oxide                                                  | 2 mg/m <sup>3</sup> TWA                                                                                                                                                                                                      | 5 mg/m <sup>3</sup> PEL                                                                                                                                                                                                                            | None      | None  |
| Petroleum distillates, hydrotreated, light naphthenic          | 5 mg/m <sup>3</sup> TWA Inhalable fraction.                                                                                                                                                                                  | 5 mg/m <sup>3</sup> PEL Mist.<br>500 ppm (2,000 mg/m <sup>3</sup> ) PEL                                                                                                                                                                            | None      | None  |
| Aluminum not powder, dust or fume                              | 1 mg/m <sup>3</sup> TWA Respirable fraction.                                                                                                                                                                                 | None                                                                                                                                                                                                                                               | None      | None  |
| White mineral oil (petroleum) (not cmr)                        | Included in the regulation but with no data values. See regulation for further details<br>Exposure by all routes should be carefully controlled to levels as low as possible.<br>5 mg/m <sup>3</sup> TWA Inhalable fraction. | 5 mg/m <sup>3</sup> PEL Mist.                                                                                                                                                                                                                      | None      | None  |
| Quartz (SiO <sub>2</sub> ) respirable particulates (RCS) >=10% | 0.025 mg/m <sup>3</sup> TWA Respirable fraction.                                                                                                                                                                             | 0.05 mg/m <sup>3</sup> TWA (Respirable dust.)<br>(Respirable dust.)<br>0.025 mg/m <sup>3</sup> OSHA ACT<br>(Respirable dust.)<br>0.05 mg/m <sup>3</sup> PEL Respirable dust.<br>2.4 MPPCF TWA Respirable.<br>0.1 mg/m <sup>3</sup> TWA Respirable. | None      | None  |

**Engineering controls:**

Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

**Respiratory protection:**

Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

**Eye/face protection:**

Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available.

**Skin protection:**

Use impermeable gloves and protective clothing as necessary to prevent skin contact.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Physical state:**

Paste

**Color:**

Silver

**Odor:**

Hydrocarbon-like

**Odor threshold:**

Not available.

**pH:**

Not applicable

**Vapor pressure:**

< 5 mm hg

**Boiling point/range:**

Not available.

**Melting point/range:**

Not available.

**Specific gravity:**

1.25

IDH number: 235005

Product name: LOCTITE LB 8150 SV A/S known as Silver Grade Anti-Seize Lubric

|                                                 |                      |
|-------------------------------------------------|----------------------|
| <b>Vapor density:</b>                           | Not available.       |
| <b>Flash point:</b>                             | > 93 °C (> 199.4 °F) |
| <b>Flam mable/Explosive limits - lower:</b>     | Not available.       |
| <b>Flam mable/Explosive limits - upper:</b>     | Not available.       |
| <b>Autoignition temperature:</b>                | Not determined       |
| <b>Flam mability:</b>                           | Not applicable       |
| <b>Evaporation rate:</b>                        | Not available.       |
| <b>Solubility in water:</b>                     | Insoluble            |
| <b>Partition coefficient (n-octanol/water):</b> | Not available.       |
| <b>VOC content:</b>                             | < 3 %                |
| <b>Viscosity:</b>                               | Not available.       |
| <b>Decom position temperature:</b>              | Not available.       |

## 10. STABILITY AND REACTIVITY

|                                          |                                                                                          |
|------------------------------------------|------------------------------------------------------------------------------------------|
| <b>Stability:</b>                        | Stable under normal conditions of storage and use.                                       |
| <b>Hazardous reactions:</b>              | None under normal processing.                                                            |
| <b>Hazardous decomposition products:</b> | Oxides of carbon. Irritating organic vapours.                                            |
| <b>Incompatible materials:</b>           | Strong oxidizing agents. Acids. Water. Alkalis. Hydrogen fluoride. Phosphorus Compounds. |
| <b>Reactivity:</b>                       | Not available.                                                                           |
| <b>Conditions to avoid:</b>              | Keep aw ay from heat, ignition sources and incompatible materials.                       |

## 11. TOXICOLOGICAL INFORMATION

|                                     |                                   |
|-------------------------------------|-----------------------------------|
| <b>Relevant routes of exposure:</b> | Skin, Inhalation, Eyes, Ingestion |
|-------------------------------------|-----------------------------------|

### Potential Health Effects/Symptoms

|                      |                                                                                                                                                                                                                                          |
|----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Inhalation:</b>   | May cause respiratory tract irritation. Abrasion of cured material such as by sanding or grinding could release respirable particles of silica quartz, a cancer hazard by inhalation. Normal use of this product causes no such release. |
| <b>Skin contact:</b> | Causes skin irritation.                                                                                                                                                                                                                  |
| <b>Eye contact:</b>  | Causes serious eye damage.                                                                                                                                                                                                               |
| <b>Ingestion:</b>    | Not expected under normal conditions of use. May cause gastrointestinal tract irritation if swallowed.                                                                                                                                   |

| Hazardous Component(s)                                 | LD50s and LC50s                                                                                                                                                                                                                                                                                       | Immediate and Delayed Health Effects   |
|--------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------|
| Distillates (petroleum), hydrotreated heavy naphthenic | Inhalation LC50 (Rat, 4 h) = > 4.026 mg/l<br>Inhalation LC50 (Rat, 4 h) = 2.18 mg/l<br>Inhalation LC50 (Rat, 4 h) = 10.5 mg/l<br>Inhalation LC50 (Rat, 4 h) = > 5.2 mg/l<br>Inhalation LC50 (Rat, 4 h) = < 5.7 mg/l                                                                                   | Irritant                               |
| Graphite                                               | Inhalation LC50 (Rat, 4 h) = > 2,000 mg/m3<br>Inhalation LC50 (Rat, 4 h) = > 2,000 mg/m3                                                                                                                                                                                                              | Lung                                   |
| Calcium oxide                                          | Inhalation LC50 (Rat, 4 h) = 40 mg/m3<br>Inhalation LC50 (Rat, 4 h) = 160 mg/m3                                                                                                                                                                                                                       | Irritant, Corrosive, Eyes              |
| Petroleum distillates, hydrotreated, light naphthenic  | Inhalation LC50 (Rat, 4 h) = 10.5 mg/l<br>Inhalation LC50 (Rat, 4 h) = > 4.026 mg/l<br>Inhalation LC50 (Rat, 4 h) = > 5.2 mg/l<br>Inhalation LC50 (Rat, 4 h) = 9.6 mg/l<br>Inhalation LC50 (Rat, 4 h) = 2.18 mg/l<br>Inhalation LC50 (Rat, 4 h) = > 5 mg/l<br>Inhalation LC50 (Rat, 4 h) = < 5.7 mg/l | Irritant                               |
| Aluminum not powder, dust or fume                      | Inhalation LC50 (Rat, 4 h) = > 0.888 mg/l                                                                                                                                                                                                                                                             | Central nervous system, Irritant, Lung |
| White mineral oil (petroleum) (not cmr)                | Inhalation LC50 (Rat, 4 h) = > 5 mg/l                                                                                                                                                                                                                                                                 | No Data                                |
| Quartz (SiO2) respirable particulates (RCS) >=10%      | None                                                                                                                                                                                                                                                                                                  | No Data                                |

| Hazardous Component(s)                                 | NTP Carcinogen                | IARC Carcinogen | OSHA Carcinogen (Specifically Regulated) |
|--------------------------------------------------------|-------------------------------|-----------------|------------------------------------------|
| Distillates (petroleum), hydrotreated heavy naphthenic | No                            | No              | No                                       |
| Graphite                                               | No                            | No              | No                                       |
| Calcium oxide                                          | No                            | No              | No                                       |
| Petroleum distillates, hydrotreated, light naphthenic  | No                            | No              | No                                       |
| Aluminum not powder, dust or fume                      | No                            | No              | No                                       |
| White mineral oil (petroleum) (not cmr)                | No                            | No              | No                                       |
| Quartz (SiO2) respirable particulates (RCS) >=10%      | Known To Be Human Carcinogen. | Group 1         | Yes                                      |

## 12. ECOLOGICAL INFORMATION

**Ecological information:** Not available.

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Follow all local, state, federal and provincial regulations for disposal.

## 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

|                                  |               |
|----------------------------------|---------------|
| <b>Proper shipping name:</b>     | Not regulated |
| <b>Hazard class or division:</b> | None          |
| <b>Identification number:</b>    | None          |
| <b>Packing group:</b>            | None          |

#### International Air Transportation (ICAO/IATA)

|                           |               |
|---------------------------|---------------|
| Proper shipping name:     | Not regulated |
| Hazard class or division: | None          |
| Identification number:    | None          |
| Packing group:            | None          |

#### Water Transportation (IMO/IMDG)

|                           |               |
|---------------------------|---------------|
| Proper shipping name:     | Not regulated |
| Hazard class or division: | None          |
| Identification number:    | None          |
| Packing group:            | None          |

### 15. REGULATORY INFORMATION

#### United States Regulatory Information

|                                         |                                                                                                                      |
|-----------------------------------------|----------------------------------------------------------------------------------------------------------------------|
| <b>TSCA 8 (b) Inventory Status:</b>     | All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory. |
| <b>TSCA 12 (b) Export Notification:</b> | None above reporting de minimis                                                                                      |
| <b>CERCLA/SARA Section 302 EHS:</b>     | None above reporting de minimis.                                                                                     |
| <b>CERCLA/SARA Section 311/312:</b>     | Immediate Health                                                                                                     |
| <b>CERCLA/SARA Section 313:</b>         | None above reporting de minimis.                                                                                     |
| <b>California Proposition 65:</b>       | This product contains a chemical known in the State of California to cause cancer.                                   |

#### Canada Regulatory Information

|                              |                                                                                                   |
|------------------------------|---------------------------------------------------------------------------------------------------|
| <b>CEPA DSL/NDSL Status:</b> | All components are listed on or are exempt from listing on the Canadian Domestic Substances List. |
|------------------------------|---------------------------------------------------------------------------------------------------|

### 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 2,3,8,11,13,15

**Prepared by:** Product Safety and Regulatory Affairs

**Issue date:** 06/23/2021

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.