亚泰化工
YATAI CHEMICAL

江苏亚泰化工有限公司
Jiangsu Yatai Chemical Co.,Ltd
IATF16949, ISO9001, ISO14001,ISO45001 Qualified

VP latex

The VP latex is a terpolymer of Styrene,Butadiene and 2-Vinyl Pyridine monomer. with better adhesion,it used for dipping of Nylon, Rayon, Polyester fabrics & other Textile reinforcement materials,which provides excellent adhesion between dipped Fabrics and Rubber Compound.

Applications:

Dipping of fabric for tire, conveyor belt and other textile reinforced rubber based products.

Packing:

200kg plastic drums, 1000kg IBC, 20000kg Flexible Tank.

Transportation and Storage :

Transportation and store between temperature of 0-40℃, protect from freezing and direct exposure to sunlight, keep containers closed when not used; Shelf life of 6monthes from production date under good storage condition.

PROPERTIES	Specifications	Testing Methods
Appearance	Milky white emulsion	
TSC(Solid content),%	40.5±1	SH/T 1154-2011
pH at 25°C	10-12	SH/T 1150-2011
Brookfield Viscosity, mPa·s	25-60	SH/T 1152-2014
Density, g/cm^3	0.98-0.99	SH/T 1155-1999
Mechanical Stability	≤2.0	SH/T 1151- 1992
Chemical Stability	≤0.1	Q/320205 GLFF01-2013
Coagulum	≤0.01	SH/T 1153-2011
Surface tension	40.0-60.0	SH/T 1156-2014

Note: The specifications is for our Standard form, we can also adjusting the specifications according to your special request.