Tapmatic[®] Edge Crème

Cutting Fluid



FEATURES

- Safe on all metals
- Ecological and economical ٠
- Does not contain any hazardous chemicals
- For use when drilling, tapping blind holes, forming, bending, pre-coating fasteners, and lubricating rubber seals
- Squeeze tube allows easy application
- Excellent for vertical applications

APPLICATIONS

- Boring

- Broaching Drilling

- Tapping

• Engraving

Grinding

• Milling Threading • Turning

Drawing

Reaming

Facing

SPECIFICATIONS AND APPROVALS

Delta Airlines • Ford Motor Co. • General Motors Co.

PROPERTIES

FROFERIES				
Appearance / Physical State	Viscous Paste. Solid			
Odor	Slight. Soapy			
Melting / Freezing Point	Not established			
Boiling Point / Range	631.4°F (333°C) (estimated)			
Vapor Pressure	Not established			
Partition Coefficient	Not established			
Percent volatile	15 - 16%			
Flammability	Not established			
Propellant	N/A			
VOC Content	0 % per State and Federal Consumer Product Regulations			
Color	Opaque.			
Flash Point	> 199.40°F (> 93.00°C) Tag Closed Cup			
Density	Not established			
Evaporation Rate	Not established			
Vapor density	Not established			
Auto-Ignition Temperature	Not established			
Viscosity	Not established			
Specific Gravity	0.87 - 0.89 @ 20°C			
	Not established			
Temperature Range				
4-Ball Weld Load	Not established			

DIRECTIONS

Apply a few drops of creme prior to contact.

HANDLING

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get this material in contact with eyes. Do not get this material in contact with skin. Avoid prolonged exposure. Do not get this

material on clothing. Do not use in areas without adequate ventilation. Wear personal protective equipment. Observe good industrial hygiene practices. Wash thoroughly after handling. Use care in handling/storage.

STORAGE

Keep tightly closed in a dry, cool and well-ventilated place. Keep out of the reach of children. Use care in handling/storage.

DISPOSAL

This product, in its present state, when discarded or disposed of, is not a hazardous waste according to Federal regulations (40 CFR 261.4 (b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria for hazardous waste.

AVAILABLE PRODUCTS

Part No.			C		
US	Canada	Net Contents	Container Type	Units/Case	Case Weight
43100	C43100	10 fl oz / 0.296 L	tube	10	7 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS[®], SCRUBS[®], DYKEM[®], Accu-Lube[®], DYMON[®], Spray Nine[®], and Cedar[®] are registered trademarks and Rustlick[™], Diamondkote[™], and MetalMates[™] are trademarks of Illinois Tool Works • All Rights Reserved