

ACC 2210

	ALL 221U
Product Group	Cleaner
Description	ACC 2210 is an alkaline, yellow cleaner for all metal, plastic and painted surfaces of aircraft.
Characteristics	Easy to mix with water
	Applied by spray or as foam by air injection.
	Nontoxic
	Nonflammable
	Biodegradable
Specifications	AMS 1526C AMS 1550B
Application	Exterior cleaning:
	For general cleaning mix 1 part of ACC 2210 with 9 parts by volume of water.
	For heavy duty cleaning mix 1 part of ACC 2210 with 3 parts by volume of water.
	For very greasy surfaces mix 1 part of ACC 2210 with 3 parts by volume of water. Add 12 parts by volume of ACC 4400.
	Do not allow to dry before rinsing
	Interior Cleaning:
4	Mix 1 part of ACC 2210 with 20-50 parts by volume of water.
	Apply mixture with spray or mop. Wait for 5-10 minutes, agitate with a

Toxicity and Hazards

Before use always refer to MATERIAL SAFETY DATA SHEET for precautionary, handling and first aid information.

Protective clothing, made from alkali resistant materials, must be worn when working with this cleaner.

May cause eye and skin irritation.

brush or mop and rinse before it dries.

Use with adequate ventilation.

Do not swallow.

Be careful when opening containers to avoid spurting of contents.

Dispose of ACC 2210 mix with dirt residues per applicable regulations. Refer to MATERIAL SAFETY DATA SHEET for additional disposal information.

Storage

Shelf life/Packing

Store at a temperature between 5-35°C.

24 Months/ 25 KG Pail