

ACC 4410

Product Group	Solvent cleaner
Description	ACC 4410 is an alternative to MEK
Characteristics	Non-corrosive to ferrous and nonferrous metals. Very suitable for removal of oil affected areas.
Specification	AMS 1525D
Application	Use as received. Apply to metal surfaces, using clean cloths, prior to surface treatments. Keep cloth saturated with ACC 4410. Change cloth frequently. Remove residues with clean cloth.
Toxicity and Hazards	Before use always refer to MATERIAL SAFETY DATA SHEET for precautionary, handling and first aid information. Protective clothing, made from solvent resistant materials, must be worn when working with this solvent May cause eye and skin irritation. Avoid exposure to high concentrations of vapor. Use with adequate ventilation. Do not use where ignition sparks may occur because fire hazards. Be careful when opening containers to avoid spurting of contents. Dispose of ACC 4410 mix with residues per applicable regulations. Refer to MATERIAL SAFETY DATA SHEET for additional disposal information. Do not keep near oxidizing materials.
Storage	Store in closed containers at temperatures between 5-35°C.
Shelf life/Packing	24 Months/ 20 Liter Pail

Notice

The provided information in this document is given in good faith and based on our current knowledge. It is indicative information only and never binding. It must on no account be used as a substitute for necessary preliminary tests that must ensure the suitability of our product

TDS 4410- 02/13