

### NOXIT® 86



# Product description:

# "FOGGING" CORROSION INHIBITING COMPOUND

#### **FEATURES:**

A heavy duty, water displacing, non-drying, thin film, corrosion preventive compound

#### **KEY BENEFITS:**

- Contains no ozone depleting chemicals
- Contacts corrosion in all areas of the airplane
- Integral part of the corrosion control program
- Does not harm most paints, plastics, or insulation

# Noxit® 86 A non-drying, water displacing corrosion preventive compound FOR HIGHLY CRITICAL METAL SURFACES Noxit® 86 Anon-drying, water displacing corrosion preventive compound FOR HIGHLY CRITICAL METAL SURFACES Noxit® 86 Anon-drying, water displacing corrosion preventive compound For HIGHLY CRITICAL METAL SURFACES Noxit® 86 Anon-drying, water displacing corrosion preventive compound For HIGHLY CRITICAL METAL SURFACES Noxit® 86 Anon-drying, water displacing corrosion preventive compound For HIGHLY CRITICAL METAL SURFACES Noxit® 86 Anon-drying and displacing corrosion preventive compound For HIGHLY CRITICAL METAL SURFACES Noxit® 86 Anon-drying and displacing corrosion preventive compound For HIGHLY CRITICAL METAL SURFACES

- Prevents corrosion
- Provides light lubrication
- Useful for initial protection during shipment and storage as well as inservice treatment of critical areas
- Protects cables and interior and exterior aircraft surfaces

#### **SPECS:**

- Class 2, Grade 134A
- NSN: 8030-01-524-0114
- QPL for Mil-PRF-81309H Type II & III

Rev: 29072F 11-30-2021







## NOXIT® 86



# Product description:

"FOGGING" CORROSION INHIBITING COMPOUND

#### **APPLICATIONS:**

- ✓ When used in conjunction with the Formit®-18-90-FOG or Formit® -18-STD-FOG, the Noxit® 86 aerosol can form a corrosion inhibiting fog which will coat hard to reach areas
- ✓ One aerosol will cover about 70ft² (6.5 m²) at the recommended thickness
- ✓ Use on highly critical metal surfaces and cables
- ✓ Suitable for service use due to its complete miscibility with lubricating oil and ease of application

#### PHYSICAL PROPERTIES:

Boiling Range: -22°F to 375°F (-30°C to 190°C)

**Evaporation Rate:** Faster than ether

► Flame Extension: Flammable

► Material V.O.C.: 186 G/L (1.5 Lbs/Gal)

Specific Gravity (H<sub>2</sub>O=1): 1.1

Vapor Density: Heavier than air







# NOXIT® 86



# **Product description:**

"FOGGING" CORROSION INHIBITING COMPOUND

#### **AVAILABLE PACK SIZES:**

- Case of 12 of 15 fl oz (444 ml) Aerosols-002049
- Case of 4 each Gallon (4 each of 3.8L) Cans-008997
- 5 Gallon (18.9L) Pail-008998
- ▶ 55 Gallon (208L) Drum-008999
- Special Packaging Upon Request

