

D-5460NS



Product description:

MOLY DRI-LUBE ZERO OZONE DEPLETING

FEATURES:

- A resin-bonded system of molybdenum disulfide powder that is dispersed in a thermoplastic resin which air dries in 5-10 minutes
- Contains a dry film
- An extreme pressure lube

KEY BENEFITS:

- Excellent high temperature stability
- Good surface adhesion
- Excellent for use as a break-in lube, rubber anti-seize, and gasket coating
- Contains a fast air drying formula
- Has a clean and uncontaminated delivery system
- Formulation yields a thin but durable abrasion resistant coating that is effective up to 660°F (350°C)

SPECS:

- GE/DFO: A50 TF192 Class C-6, 192-58
- UAL#: LUB-4500-12SC
- NSN: 9150-01-057-2576 (16 fl oz (473 ml) Aerosol)

Rev: 20067G 11-30-2021







D-5460NS



Product description:

MOLY DRI-LUBE ZERO OZONE

DEPLETING

APPLICATIONS:

- ✓ **D-5460NS** can be used in conjunction with the **Formit®** extensions to provide targeted spray to areas that may be difficult to reach but need to be coated. Please refer to the **Formit®** technical data sheet for more information.
- ✓ Bulk application available as ZC-460
- ✓ Originally formulated for DC-8 flap track fairings
- ✓ **D-5460NS** is used in aircraft applications, which includes DC-10 elevator bus support system parts (springs and quick tubes) and engine applications, such as fan rotor assembly and fan reverser precooler duct seal lubrication

PHYSICAL PROPERTIES:

► Average Particle Size: MoS₂ 0.4 Microns (0.01 Mils)

▶ Boundary Lubrication: 660°F (350°C)

Coefficient of Friction: 0.23 (Static)

Color: Gray

Fungal Growth per Fed-STD-810 Method 508.7: 0 (No Microbial Growth)

Service Temperature: 390°F (200°C)







D-5460NS



Product description:

MOLY DRI-LUBE ZERO OZONE DEPLETING

AVAILABLE PACK SIZES:

- Case of 12 of 16 fl oz (473 ml) Aerosols-002061
- Case of 4 each Gallon (4 each of 3.8L) Cans-002318
- Special Packaging Upon Request

